



FENCE STANDARD SPECIFICATIONS – V1.0

Corners:

H-Braces, Pull Posts: Vertical members:

2 7/8" dia Pipe Schedule 40 or equivalent Round Tube SS 40 High Strength, Galvanized Steel, post caps to be stamped steel or malleable steel with hot dip galvanized finish.

Horizontals and Diagonal members:

2 3/8" SS 40 or equivalent, High Strength, Galvanized Steel

Welds:

Field welds 70 ksi, full fillet welds with field applied touch-up of Aluminized Industrial Coating

Line Posts:

Vertical Members: 2 3/8" dia, Pipe Schedule 40 or equivalent Round Tube SS 40 High Strength, Galvanized Steel

Mesh Infill:

Fixed Knot Game Fence, 12.5 ga Top, Bottom and Main wire, Class 3 Galvanized, High Tensile, 6" vertical Stay Spacing, 96" H, graduated horizontal spacing at 3"(6), 4"(2), 5"(2), 6"(3), 7"(6) and 8"(3).

Bottom Wire:

Predator Wire 15.5 ga, Class 3 Galvanized, High Tensile, 4-Point Barb, 3" o.c.

Tejas Ranch & Game Fence

903.292.0525

401 S. Palestine, #188, Athens TX 75751

www.TejasRanchFence.com

john@TejasRanchFence.com