



## **FENCE STANDARD SPECIFICATIONS – V1.0**

### **Corners:**

H-Braces, Pull Posts: Vertical members:

2 7/8" dia Pipe Schedule 40 or equivalent Round Tube SS 40 High Strength, Galvanized Steel, post caps to be stamped steel or malleable steel with hot dip galvanized finish.

### **Horizontals and Diagonal members:**

2 3/8" SS 40 or equivalent, High Strength, Galvanized Steel

### **Welds:**

Field welds 70 ksi, full fillet welds with field applied touch-up of Aluminized Industrial Coating

### **Line Posts:**

Vertical Members: 2 3/8" dia, Pipe Schedule 40 or equivalent Round Tube SS 40 High Strength, Galvanized Steel

### **Mesh Infill:**

Fixed Knot Game Fence, 12.5 ga Top, Bottom and Main wire, Class 3 Galvanized, High Tensile, 6" vertical Stay Spacing, 96" H, graduated horizontal spacing at 3"(6), 4"(2), 5"(2), 6"(3), 7"(6) and 8"(3).

### **Bottom Wire:**

Predator Wire 15.5 ga, Class 3 Galvanized, High Tensile, 4-Point Barb, 3" o.c.

**Tejas Ranch & Game Fence**

**903.292.0525**

401 S. Palestine, #188, Athens TX 75751

[www.TejasRanchFence.com](http://www.TejasRanchFence.com)

[john@TejasRanchFence.com](mailto:john@TejasRanchFence.com)